

ANDROMEDA P LED

IP44 Budget Range Recessed LED Downlights with Opal Diffuser



Type:	Budget range recessed LED downlights with opal diffuser.
Specification:	Opal diffuser with IP44 protection rating. Aluminium body in white finish. Tool free spring clip installation. Luminaire is plastic-wrapped and boxed individually.
Installation:	Suitable for plasterboard or similar types of ceiling, requires a cut-out.
Application:	Indoor. Decorative lighting for shops, displays, interiors, offices, receptions and other public areas.

Name	Overall dimensions (cut-out), mm	Lifetime	Luminaire output*, lm Ta=25°C	System power*, W	CRI (Ra)	CCT, K	Weight, kg
Andromeda P LED1x700 D522 T830 OP	Ø92(75)x64	40000	660	7	80+	3000	0,11
Andromeda P LED1x1000 D523 T830 OP	Ø113(95)x73	40000	930	10	80+	3000	0,16
Andromeda P LED1x1400 D524 T830 OP	Ø174(150)x79	40000	1330	14	80+	3000	0,28
Andromeda P LED1x2100 D525 T830 OP	Ø244(200)x95	40000	1960	20	80+	3000	0,53
Andromeda P LED1x700 D522 T840 OP	Ø92(75)x64	40000	700	7	80+	4000	0,11
Andromeda P LED1x1000 D523 T840 OP	Ø113(95)x73	40000	980	10	80+	4000	0,16
Andromeda P LED1x1400 D524 T840 OP	Ø174(150)x79	40000	1400	14	80+	4000	0,28
Andromeda P LED1x2100 D525 T840 OP	Ø244(200)x95	40000	2060	20	80+	4000	0,53

* Tolerance range for optical and electrical data: ±10 %

Options available on request:

- OP- Opal diffuser
- T830- Colour temperature 3000K
- T840- Colour temperature 4000K

Andromeda P LED1x1400 D524 T840 OP

