

# PRODUCT DATASHEET

## O FACADE UPDOWN 12 W 3000 K IP54 GY

OUTDOOR FACADE UPDOWN | Luminaires with classic shape and light outlet up and down



---

### AREAS OF APPLICATION

- Outdoor
- Building facades
- Decorative illumination

---

### PRODUCT BENEFITS

- Energy-efficient thanks to LED technology
- 5 years guarantee
- Easy and quick installation
- Homogeneous light output

---

### PRODUCT FEATURES

- Very bright and functional outdoor LED luminaires
- Type of protection: IP54
- Die-cast aluminum housing
- Available in two housing colors: white and dark gray
- Diffuser made of clear glass



**TECHNICAL DATA**

Electrical data

<b>Operating mode</b>	Mains voltage
<b>Mains frequency</b>	50/60 Hz
<b>Power factor <math>\lambda</math></b>	0.5
<b>Nominal wattage</b>	12.00 W
<b>Nominal voltage</b>	220...240 V
<b>Nominal current</b>	0.055 A


Photometrical data

<b>Color temperature</b>	3000 K
<b>Luminous efficacy</b>	60 lm/W
<b>Luminous flux</b>	700 lm
<b>Light color (designation)</b>	Warm White
<b>Color rendering index Ra</b>	$\geq 80$
<b>Standard deviation of color matching</b>	6 sdc <sub>m</sub>

Light technical data

<b>Beam angle</b>	280.00 °
-------------------	----------

— Dimensions & weight



<b>Length</b>	55.0 mm
<b>Width</b>	90.0 mm
<b>Height</b>	160.0 mm
<b>Product weight</b>	480.00 g

Colors & materials

<b>Housing color</b>	Gray
<b>Product color</b>	Gray

<b>Body material</b>	Aluminum
<b>Cover material</b>	Glass

### Temperatures & operating conditions

<b>Ambient temperature range</b>	-20...40 °C
----------------------------------	-------------

### Lifespan

<b>Number of switching cycles</b>	15000
<b>Lifespan L70 at 25 °C</b>	30000 h
<b>Lifespan L80 at 25 °C</b>	- h
<b>Lifespan L90 at 25 °C</b>	- h

### Additional product data

<b>Mounting type</b>	Surface
<b>Mounting location</b>	Wall


### Capabilities

<b>Dimmable</b>	No
<b>Type of connection</b>	Screw terminal, 3-Pole
<b>LED module replaceable</b>	Not replaceable

### Certificates & standards

<b>Type of protection</b>	IP54
<b>Protection class</b>	I
<b>Protection class IK (shock resistance)</b>	IK06
<b>Glow Wire Test according to IEC 695-2-1</b>	-
<b>Photobio. safety group acc. to EN62471</b>	RG 0
<b>Luminaire with limited surface temperature, class "D"</b>	-
<b>Standards</b>	CE

Light Distribution



LDC typ polar

EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075075054	Folding carton box 1	74 mm x 109 mm x 180 mm	503.00 g	1.45 dm <sup>3</sup>
4058075075061	Shipping carton box 6	245 mm x 240 mm x 195 mm	3193.00 g	11.47 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

REFERENCES / LINKS

For Guarantee see  
 ▶ [www.ledvance.com/guarantee](http://www.ledvance.com/guarantee)

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.